Use this browser's print function to print this entire page, then close this window.

Catalog Page 31-1

.100"	Socket	Single Row - Screw Machine Contacts for .025"	Right Angle	Thru Hole

.100" Centers, Single Row Right Angle, accepting .025" Square Pin, Screw Machine Socket



Mates With	A		B		C		D		E		Number of Positions	
	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch		
1012K	8.13	0.320	6.86	0.270	5.20	0.126	5.79	0.228			G2 - Y	1.40

Technical Notes	
Contact Material:	Shell: Phosphor Bronze, Contact Clip: 6 finger BeCu [447]
Insulation Material:	Thermoplastic, UL 94V-0 rated, Black
Insulation Resistance:	5,000 MegOhm @ 500VDC
Current Rating:	3 amp continuous @ 100 VDC/contact
Max Processing Temp:	125°C for 60 seconds
Insertion Force:	200 grams (7.0 oz) (typ initial per w/ .025" sq pin) 6 finger contact [447]
Extraction Force:	80 grams (3.1 oz) (typ initial per w/ .025" sq pin) 6 finger contact [447]

COMM CON CONNECTORS, INC.

3648 Evergreen Street, Duarte, Ca 91010 · (626) 301-4200 · fax (626) 301-4212 · e-mail: [redacted]