


.100	Socket	Triple Row	Straight	Thru Hole
------	--------	------------	----------	-----------

.100 inch Center - 3 Row Straight - accepting .025 inch Square Pin - Socket



Base Part Number	A		B		C		D		E		Plating Options	Number of Positions
	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch		
1118	10.67	0.420	8.25	0.325	2.41	0.095	7.62	0.300			T : G2	6-120

Technical Notes	
Contact Material:	Contact: 2 Finger Stamped - Phosphor Bronze
Insulation Material:	Glass Filled Nylon 46 - UL 94V-0 rated - Black (std)
Heat Deflection:	260°C @ 264 PSI per ASTM D648
Insulation Resistance:	5000 MegOhm @ 500VDC
Current Rating:	2 amp continuous @ 100 VDC/contact
Max Processing Temp:	150°C for 60 seconds
Insertion Force:	67 grams (2.4oz) (typ initial force per contact w/ .025 inch sq pin)
Extraction Force:	47 grams (1.7 oz) (typ initial force per contact w/ .025 inch sq pin)
Plastic:	High Temperature Compatible

COMM CON CONNECTORS INC.
 1848 Evergreen Street, Duarte, Ca 91010 · (626) 301-4200 · fax (626) 301-4212 · e-mail:
info@commcon.com